



Pawling Corporation
32 Nelson Hill Road
PO Box 200
Wassaic, NY 12592
sales@pawling.com

Tel. 800-431-3456
Fax 800-377-4403
Tel. 845-373-9300
Fax 845-373-7827

ARCHITECTURAL PRODUCTS DIVISION

Wall Protection Systems
Entrance Mats And Gratings
Athletic Flooring Systems
Industrial Impact Protection Systems
Parking And Traffic Safety Products

MR Credit 4.1/4.2 Recycled Content, WG-4 Wall Guard

The WGV-4 wall guard consists an extruded aluminum retainer, an extruded thermoplastic snap-on cover, and an extruded flexible impact cushion. The cover is designed to work in conjunction with the retainer and impact cushion such that the assembly will absorb significant impact without damage to the materials or surrounding construction.

The recycled content of this product is given as a percentage calculated by comparing the weight of the product to the weight of the recycled materials it contains. The net weight of the wall guard assembly is .91 pounds per linear foot. This value represents the sum of the weights of retainer and cover extrusions combined and is subject to variation resulting from standard manufacturing tolerances.

The recycled content of this wall guard is contained solely in the retainer as follows:

Post Consumer Scrap:	10%
Post Industrial Scrap:	60%
Primary Aluminum:	30%

In accordance with guidelines set forth in USGBC – LEED V2.2, the recycled content of the retainer is:

$$\text{Post-Consumer} + 1/2 * \text{Pre-Consumer} = 10\% + 1/2 * 60\% = 40\%$$

Applying this percentage to the weight of the retainer, the recycled content of the wall guard assembly is 23% of the product by weight $((40\% * .53) / .91 = 23\%)$. This value may be applied to the project cost of this product and added to similar values for the total project in order to determine LEED credit applicability for MR Credits 4.1 and 4.2.