



**Pawling Corporation**  
32 Nelson Hill Road  
PO Box 200  
Wassaic, NY 12592  
[sales@pawling.com](mailto:sales@pawling.com)

Tel. 800-431-3456  
Fax 800-377-4403  
Tel. 845-373-9300  
Fax 845-373-7827

**ARCHITECTURAL PRODUCTS DIVISION**

Wall Protection Systems  
Entrance Mats And Gratings  
Athletic Flooring Systems  
Industrial Impact Protection Systems  
Parking And Traffic Safety Products

## Adirondack Wood Care Instructions

**Remove Dust** – Dust buildup is made of small airborne particles and may scratch or dull the surface if it is not removed correctly. Simply wipe the surface with a cloth dampened with cleaning polish or mild detergent.

**Clean** – Fingerprints, cooking fumes, smoking residue, etc., can accumulate on any surface. None of these contaminants will harm the finish, however, they should be periodically removed to restore the finish to its original luster. Simply wipe the surface with a damp cloth dampened with a non-wax containing polish or a mild detergent solution. Avoid the use of ammonia-based products or silicone oils as they may cause damage to the finish if they are used over a long period of time.

**Spills** – The finish, which has been applied by our firm, is very durable and resistant to most household spills. All spills, however, should be wiped up promptly to avoid any potential damage to the finish.

**Environmental Exposure** – Any excessive prolonged exposure to direct sunlight, high temperatures or high humidity can cause damage to both the finish and the wood itself. The finish that we have applied should be treated as any fine wood furniture finish. Any extreme environmental exposure should be avoided.