



Pawling Corporation
32 Nelson Hill Road
PO Box 200
Wassaic, NY 12592
sales@pawling.com

Tel. 800-431-3456
Fax 800-377-4403
Tel. 845-373-9300
Fax 845-373-7827

ARCHITECTURAL PRODUCTS DIVISION

Wall Protection Systems
Entrance Mats And Gratings
Athletic Flooring Systems
Industrial Impact Protection Systems
Parking And Traffic Safety Products

ENTRANCE MATTING INSTALLATION INSTRUCTIONS

Berber Matting, Model EM-20
Protector Matting, Model EM-40
Jaguar Matting, Model EM-50

PRIOR TO INSTALLATION

Even though our carpet does not have to be brought to room temperature in order to be properly installed, the carpet will be more pliable and easier to work with when at room temperature or warmer.

After carpet has been rolled up for some time, it has a "memory" from being rolled up. This shows when unrolling the carpet because the carpet tends to curl either up or down (whichever way it was rolled during shipment). To remedy this, we recommend the carpet be rolled out and be brought to room temperature.

In extreme cases, we recommend the carpet be "reverse-rolled" for 24 hours.

SUB-FLOORS:

Always make sure that the carpet is installed over firm, flat, clean, smooth, hard surfaces (free or cracks or foreign substances).

INSTALLING THE CARPET:

1. Our carpet matting can be cut to any size, shape or form with a sharp razor blade knife.
2. We do recommend all installations be directly glued-down (with the exception of areas requiring looses laid, removable mats).
3. Please, refer to our adhesive recommendations below. Take time out to read the manufacturer's recommendations and follow these recommendations closely.
4. We recommend that the seams be sealed with a premium latex-based seam-sealer. (Not available from Pawling.)
5. Make sure to install the entire job with the nap all in one and the same direction. For this purpose, arrows are marked on the backside of the carpet.
6. We recommend that a 75 lb. to 100 lb. roller be used after initial installation.