


Pro•Tek® Wall Protection Systems

Architectural Building Products Since 1945

KPPS-40 Kick Plates



24

48

3

Features:

- Class A fire rating
- NFPA-252 (UL10b) approved for use on 90 minute wood and 180 minute steel fire rated door assemblies

Finishes:

- Manufacturer's standard colors
- Custom colors available

Mounting Options:

Adhesive

ADH-30 adhesive supplied separately for use on metal and wood doors

Drilled

Clearance holes for ABSS-112 #8 x 3/4" (19) oval head sheet metal screw and ABCW-132 stainless cup washer supplied separately as required

Taped

ADH-4042 double sided adhesive tape factory applied to kick plate

1" Typ.		
+	\ \	- 1" Typ. (25) -
		Clearance hole for #8 fastener

3

3

2

1

# of holes	kick plate size
6	24 x 6 to 24 x 16
8	24 x 24, 32 x 6 to 32 x 16, 48 x 6 to 48 x 16
10	32 x 24 to 48 x 24, 24 x 32, 24 x 48
12	32 x 32 to 48 x 48

^{*}Dimensions are specified as Width x Height

Optional Drilling

Pawling Corporation reserves the right to discontinue a design or modify an existing design without prior notice

Customer:	Project :	MD 120DC 0
Architect:	Sales Rep :	MD. 13053.0